

(12) INTERNATIONAL APPLICATION PUBLISHED UNDER THE PATENT COOPERATION TREATY (PCT)

(19) World Intellectual Property Organization
International Bureau



(43) International Publication Date
19 September 2002 (19.09.2002)

PCT

(10) International Publication Number
WO 02/071870 A1

(51) International Patent Classification⁷: **A23L 1/0524**,
1/10, A23P 1/16, A61K 7/15, A21D 13/08, A23G 9/02,
A62D 1/00

(21) International Application Number: PCT/EP02/01212

(22) International Filing Date: 6 February 2002 (06.02.2002)

(25) Filing Language: English

(26) Publication Language: English

(30) Priority Data:
01200722.5 26 February 2001 (26.02.2001) EP

(71) Applicant (for AE, AL, AM, AT, AZ, BA, BE, BF, BG, BJ, BR, BY, CF, CG, CH, CI, CM, CN, CO, CR, CU, CZ, DE, DK, DM, DZ, EC, EE, ES, FI, FR, GA, GE, GN, GQ, GR, GW, HR, HU, ID, IS, IT, JP, KG, KP, KR, KZ, LC, LR, LT, LU, LV, MA, MC, MD, MG, MK, ML, MR, MX, NE, NL, NO, PH, PL, PT, RO, RU, SE, SI, SK, SN, TD, TG, TJ, TM, TN, TR, UA, UZ, VN, YU only): **UNILEVER N.V.** [NL/NL]; Weena 455, NL-3013 AL Rotterdam (NL).

(71) Applicant (for AG, AU, BB, BZ, CA, CY, GB, GD, GH, GM, IE, IL, KE, LK, LS, MN, MW, MZ, NZ, OM, SD, SG, SL, SZ, TT, TZ, UG, ZA, ZM, ZW only): **UNILEVER PLC** [GB/GB]; Unilever House, Blackfriars, London, Greater London EC4P 4BQ (GB).

(71) Applicant (for IN only): **HINDUSTAN LEVER LTD** [IN/IN]; Hindustan Lever House, 165 - 166 Backbay Reclamation, 400 020 Mumbai (IN).

(72) Inventors; and

(75) Inventors/Applicants (for US only): **BRUGGEMAN**,

Yvonne, Evelien [NL/NL]; Unilever R & D Vlaardingen, Olivier van Noortlaan 120, NL-3133 AT Vlaardingen (NL). **RAVESTEIN, Peter** [NL/NL]; Unilever R & D Vlaardingen, Olivier van Noortlaan 120, NL-3133 AT Vlaardingen (NL).

(74) Agent: **VAN VELZEN, Maaïke, Mathilde**; Unilever NV, Patent Department, Olivier van Noortlaan 120, NL-3133 AT Vlaardingen (NL).

(81) Designated States (national): AE, AG, AL, AM, AT, AU, AZ, BA, BB, BG, BR, BY, BZ, CA, CH, CN, CO, CR, CU, CZ, DE, DK, DM, DZ, EC, EE, ES, FI, GB, GD, GE, GH, GM, HR, HU, ID, IL, IN, IS, JP, KE, KG, KP, KR, KZ, LC, LK, LR, LS, LT, LU, LV, MA, MD, MG, MK, MN, MW, MX, MZ, NO, NZ, OM, PH, PL, PT, RO, RU, SD, SE, SG, SI, SK, SL, TJ, TM, TN, TR, TT, TZ, UA, UG, US, UZ, VN, YU, ZA, ZM, ZW.

(84) Designated States (regional): ARIPO patent (GH, GM, KE, LS, MW, MZ, SD, SL, SZ, TZ, UG, ZM, ZW), Eurasian patent (AM, AZ, BY, KG, KZ, MD, RU, TJ, TM), European patent (AT, BE, CH, CY, DE, DK, ES, FI, FR, GB, GR, IE, IT, LU, MC, NL, PT, SE, TR), OAPI patent (BF, BJ, CF, CG, CI, CM, GA, GN, GQ, GW, ML, MR, NE, SN, TD, TG).

Published:

- with international search report
- before the expiration of the time limit for amending the claims and to be republished in the event of receipt of amendments

For two-letter codes and other abbreviations, refer to the "Guidance Notes on Codes and Abbreviations" appearing at the beginning of each regular issue of the PCT Gazette.

WO 02/071870 A1

(54) Title: PROCESS FOR THE PREPARATION OF A FOAMED PRODUCT AND PRODUCTS OBTAINABLE BY THIS PROCESS

(57) Abstract: Foamed products based on an aqueous composition comprising an oxidised feruloylated polymer are stable both during storage and after freezing and subsequent storage. A process for preparing these products is provided.

Process for the preparation of a foamed product and products obtainable by this process

Field of the invention

5

The invention relates to a formulation and process for providing foamed products which are freeze-thaw stable and also storage stable.

10 Background of the invention

The object of providing a freeze-thaw stable foam which is also storage stable has been addressed in the art.

15 US 5,384,145 relates to a whipped topping based on an aqueous solution of whey protein isolate or concentrate which has a low fat content of from 8% to 15% and has an overrun in excess of 250%, which is freeze-thaw stable and refrigerator stable for 21 days and shows good whippability.

20

However these compositions are not stable if oil is not included in their composition. Furthermore the gas phase in these products is believed to be stabilised by non-covalent, physical bonding of whey protein on the gas/liquid interphase
25 which is mainly due to protein denaturation. These interactions are non covalent and hence do not provide desired long term stability of the foam.

Furthermore foamed products based on egg white are widely
30 known. However, egg white based foam is not freeze-thaw stable and not very firm.

WO-A-00/40098 discloses crosslinked pectin which is dried and as such added to an ice cream formulation. The obtained products were found to have a sol-like character meaning that it is like a dispersion of gelled particles in a liquid, and 5 did not maintain their shape upon storage at room temperature for 30 minutes or more. Under these storage conditions the products collapsed.

Hence it is an object of the invention to provide a foamed 10 product which is freeze-thaw stable, and shows a creamy, tasteless and soft mouthfeel. Preferably these products are firm and they preferably retain their shape during storage.

Summary of the invention

15

It has surprisingly been found that these features can be fulfilled by a foamed composition comprising water and an oxidised ferulylated compound prepared in a process wherein the oxidation is carried out during or after foam formation.

20

Therefore the invention relates to a process for the preparation of a foamed product comprising the steps of:

- a) providing a mixture of a liquid and a ferulylated compound
- b) incorporating a gas phase in this mixture
- 25 c) combining said mixture with an oxidant capable of oxidation of the ferulic acid groups in the ferulylated compound, preferably under conditions wherein homogeneous distribution of the oxidant in the liquid is ensured.

30 In a further aspect the invention relates to a foamed product comprising a dispersed gas phase and a liquid phase comprising an oxidised ferulylated compound in an amount of from 1 to 20 wt% on total weight of the liquid phase, obtainable by the

above process.

In a further aspect the invention relates to food products comprising these foamed products.

5

Detailed description

For the purpose of the invention a foam is defined as an emulsion-like two phase system where gas bubbles are dispersed
10 in a (sometimes relatively small) volume of liquid containing surface active molecules, preferably macromolecules. A foam can for example be formed by whipping air into an aqueous composition comprising egg white.

The foams according to the invention optionally contain an oil,
15 preferably a triglyceride oil, as a second dispersed phase.

These products may show a more mousse like structure which is more dense than a common foam structure. However these products are also encompassed in the invention.

Foams in the context of the invention differ from products with
20 a gel structure as these latter structures only comprise gas dissolved in the liquid from which the gel is derived. The current foam products comprise more gas than this level, which is determined merely by the solubility of gas in the liquid from which the gel is derived.

25

Tasteless in the context of the invention means that the foamed products have a bland taste unless flavour compositions are added. This bland taste is desired as it enables use of the foams in any type of product.

30

In the context of the invention, the terms "fat" and "oil" are used interchangeably. The term oil encompasses both triglyceride oils and diglyceride oils.

5 For the purpose of the current invention, wt% is defined as weight percent on total weight of the liquid phase of the foamed product, unless otherwise is indicated. In this calculation, the liquid phase is considered to comprise all water soluble and water dispersible ingredients and all oil or
10 ingredients that can be dissolved or dispersed therein.

The term oxidant is used to indicate an oxidising agent, which can be either a chemical oxidising agent or an enzyme. An enzyme can be used alone or in combination with a co-oxidant
15 such as hydrogen peroxide.

The invention regards a process to prepare a foamed product, on the basis of compounds containing ferulic acid groups. Care should be taken that the conditions are such that the desired
20 specific volume and firmness are reached. Especially the oxidation of the ferulic acid units should be carefully controlled.

It is known that oxidation of a ferulyolated compound under
25 quiescent conditions leads to the formation of a gel. Reference is made to WO-A-96/03440 and WO-A-98/22513. Hence in the absence of any other measures, the blending of ferulyolated compound and an oxidant which is sufficiently powerful to enable oxidation of the ferulic acid units, will lead to the
30 formation of a gel.

It has surprisingly been found that if a gas phase is incorporated in a liquid comprising a ferulyolated compound, under simultaneous oxidation and/or followed by oxidation, a foamed product results which is freeze-thaw stable, storage 5 stable and shows the desired taste and mouth feel upon consumption.

Therefore in one aspect the invention relates to a process for the preparation of a foamed product comprising the steps of:

- 10 a) providing a mixture of a liquid and a ferulyolated compound,
- b) incorporating a gas phase in this mixture
- c) combining said mixture with an oxidant capable of oxidation of the ferulic acid groups in the ferulyolated compound, preferably under conditions wherein homogeneous distribution 15 of the oxidant in the liquid is ensured.

Without wishing to be bound by any theory, applicants believe that the oxidised ferulyolated compound acts as a surfactant and absorbs at the gas/liquid interface. In this way the 20 ferulyolated compounds are believed to be responsible for the tendency of the liquid to foam and to impart stability to the resulting foamed product. The cross linking of the ferulic acid units by oxidation is believed to fix the structure of a dispersed gas phase in a matrix of ferulyolated compounds, 25 thereby increasing the stability of the foamed product, both in terms of storage stability and in terms of freeze-thaw stability.

The process according to the invention comprises in step (b) a 30 step wherein a gas phase is incorporated into the mixture. This gas incorporation leads to the formation of a foam type structure.

- The foam type structure is prone to decline and/or collapse unless step (c) is carried out. As explained above, it is believed that in step (c) the foam structure is fixed by the 5 covalent bonds which arise from oxidation of the ferulic acid groups. Step (c) is the oxidation of ferulic acid groups. To prevent collapse of the formed foam structure, it is desired that step (c) is carried out within a short time frame, preferably in the order of seconds to at most a few minutes.
- 10 Suitable conditions to obtain this fast formation of an oxidised structure are exemplified below. Step (c) may be carried out simultaneously with the incorporation of gas in step (b) or after the gas has been incorporated. Step (c) is preferably carried out after step (b). If the oxidation is 15 carried out simultaneously, the oxidant is preferably added towards the end of step (b) when at least part of the gas has been incorporated, preferably at least 50 vol% of the gas has been incorporated.
- 20 Step (c) regards the combining of the preferably foamed mixture with an oxidant to obtain oxidation of ferulic acid groups. This combining may be carried out actively as an addition of oxidant to the mixture of step (b). Alternatively the combining may result from the formation in situ of the oxidant in the 25 mixture of step (b). In situ generation of the oxidant may for example be mediated by the action of glucose oxidase, forming hydrogenperoxide as a reaction product. Hydrogen peroxide is thus combined into the mixture.
- 30 The gas can be any gas, but is preferably selected from the group comprising air, nitrogen, carbon dioxide and ammonia gas.

The gas can be incorporated by any suitable method. Preferably the gas phase is incorporated by a method selected from the group comprising subjecting the mixture to high shear treatment, addition of a leavening system under conditions where leavening takes place, addition of an enzymatic system which leads to gas formation.

If gas is incorporated by a shear treatment, said shear treatment in step (b) is preferably a high shear treatment.

10 For the purpose of the invention shear is defined as a strain resulting from applied forces that cause or tend to cause contiguous parts of a body to slide relatively to each other in a direction parallel to their plane of contact.

It has been found that gentle shaking of a product does not lead to formation of a foam, nor does gentle mixing of the two components with a fork. Use of a home mixer at the lowest speed may lead to the formation of a foam but this will have a small overrun only.

20 For the purpose of the invention overrun is defined as the increase in volume of a product over the volume of the mix due to the incorporation of gas. For further information on overrun reference is made to Marshall et al 1996 in "Ice Cream".

25 Examples of suitable apparatus to impart shear are a turraxtm, a Hobarttm at high speed, and a scraped surface heat exchanger. Further guidance on high shear treatment is provided in the examples.

30 Preferably these apparatus are used at at least half of their maximum stirring speed to obtain a foamed product.

Preferably the shear treatment in step (b) continues for some time to increase the specific volume of the liquid to produce a foam. Preferably the shear is applied until the specific volume of the foam reaches its maximum value. The total amount of time during which shear is applied is preferably from 1 second to several minutes, more preferred from 2 seconds up to 5 minutes, most preferred from 5 seconds up to 1 minute. As a guideline it is preferred that the shear treatment is stopped once the foam has been formed and does not increase visibly in volume anymore. This can be determined quantitatively by determination of the specific volume versus time. Generally a larger volume of starting liquid requires a longer shear treatment before the maximum specific volume for the system is obtained. A skilled person will understand that the time during which shear is applied, among others also depends on the shear rate.

According to another embodiment, gas is incorporated by use of a leavening salt. Suitable leavening systems are for example described in Cereal Foods World, 41, pages 114-116, 1996 and include yeast fermentation or chemical leavening systems.

Preferably the leavening agent included in the leavening system is selected from the group of sodium bicarbonate, potassium bicarbonate, ammonium bicarbonate and disodiumpyrophosphate.

Alternatively gas is incorporated by addition of an enzymatic system generating a gas. A suitable example of such a system is the combination of a catalase and hydrogen peroxide as substrate, which will lead to the formation of oxygen gas.

The amount of gas that is included in a volume of liquid determines the specific volume of a foamed product. The foamed products according to the invention preferably show a specific

volume between about 0.01 to 0.9 g/ml, more preferred 0.1 to 0.7 g/ml. The method to determine specific volume is described in the examples.

5 Shear is preferably applied during mixing of the ferulylated compound and the oxidant in step (c). Preferably the oxidant is added to the gas phase containing mixture.
The shear applied in this step may be low or high shear as long as the shear treatment ensures that the oxidant is preferably
10 distributed homogeneously in the liquid. If the distribution is not homogeneous, only local oxidation may result and other parts of the liquid may not be oxidised and hence will not structure the foam.

15 After the incorporation of a gas in step (b) and after blending of the oxidant, preferably the foamed product is left to stand for some time, preferably 10 seconds to 1 minute to ensure that oxidation of the ferulic acid groups can take place to fix the foam that has been formed in step (b).

20

In a preferred process, the temperature during mixing in step (a) is between 10 and 40 °C.

The temperature in step (b) can be any suitable temperature. A temperature between -20 and 40 °C, preferably from 4 to 20 °C

25 is preferred.

The foamed product is preferably stored at a temperature below 25 °C, more preferred from - 20 to 25 °C.

30 Storage at increased temperature of about 50 to 90 °C is possible but was found to lead to a dried structure. After such a drying treatment at increased temperature, a brittle foam

results. This structure resembles the structure of a meringue. In a further aspect the process includes this drying step.

The oxidation may be accomplished by the action of a powerful
5 chemical oxidant such as potassium periodate, potassium permanganate, or potassium ferricyanide.

Alternatively the oxidation can be accomplished by use of an oxidising enzyme such as a peroxidase, a polyphenol oxidase
10 e.g. catechol oxidase, tyrosinase, or a laccase.

Peroxidases can be divided into those originating from plants, fungi or bacteria and those originating from a mammalian source such as myeloperoxidase and lactoperoxidase (LPO).

15 Laccases are obtainable from a variety of microbial sources notably bacteria and fungi (including filamentous fungi and yeasts), and suitable examples of laccases include those obtainable from strains of *Aspergillus*, *Neurospora* (e.g. *N. crassa*), *Prodospora*, *Botrytis*, *Collybia*, *Fomes*, *Lentinus*,
20 *Pleurotus*, *Trametes* [some species/strains of which are known by various names and/or have previously been classified within other genera], *Polyporus*, *Rhizoctonia*, *Coprinus*, *Psatyrella*, *Myceliophthora*, *Schytalidium*, *Phlebia* or *Coriolus*.

25 Preferred enzymes are selected from the group comprising horseradish peroxidase, soy bean peroxidase, *Arthromyces ramosus* peroxidase and laccases that show a redox potential of preferably more than 550 mV as described in E. Solomon et al, Chem Rev, 1996, p 2563-2605.

30

The extent of oxidation of the ferulylated compound can be measured by spectrophotometric determination of the absorbance

at 375 nm. Absorption at this wavelength is characteristic for an oxidised ferulic acid group.

In case a chemical oxidant is applied, the oxidant is preferably added in the form of a diluted aqueous solution.

5

In case an enzymatic oxidising system is applied, the enzyme is preferably added in the form of a solution or a dispersion in an aqueous buffer system. The enzymes cited above are suitable enzymes. Some enzymes, such as peroxidases require the presence
10 of a co-oxidant such as hydrogen peroxide for their activity. The co-oxidant is preferably added separately from the enzyme that requires it's presence.

The amount of enzyme added is expressed in terms of activity
15 units. Preferably enzyme is present in excess. The amount of enzyme added is preferably such that fast gelation occurs to immediately fix the foam structure created in step (b). For a peroxidase the amount of enzyme added is preferably from 50 to 10.000 units ABTS activity per ml of liquid.

20

The gas incorporation in step (b) and oxidation in step (c) can be carried out at any temperature, e.g. between -20 °C and 40 °C, preferably from 20 to 40 °C. If the oxidation is carried out enzymatically, the temperature during step (b)-(c) is
25 preferably from 20 to 40 °C. However also lower temperature are possible provided the enzyme shows activity at this temperature. Therefore most preferred the temperature is around the temperature at which the enzyme shows maximum activity.

30 Optionally oil or fat is included in the foam product. The oils and fats as listed above can suitably be included.

The oil or fat is preferably added between step (a) and (b) or during the incorporation of gas in step (b).

It is preferred that the oil or fat is added to the water phase to form a water continuous liquid instead of the reversed order
5 whereby a fat continuous system is formed.

In a further aspect the invention relates to a foamed product comprising a dispersed gas phase and a liquid phase comprising an oxidised ferulyolated compound in an amount of from 1 to 20
10 wt% on total weight of the liquid phase, obtainable by the above process.

The preferred ingredients/liquid composition as outlined below equally apply to the foamed products as prepared according to
15 the above process.

The foamed products according to the invention are freeze-thaw stable. In the context of the invention this implies that after storage at at least -20 °C for a period of at least 2 hours,
20 and subsequent thawing at room temperature (about 25 °C), the products are characterized by a specific volume which is 70 to 100% of the specific volume of the foamed product before it was stored at at least -20 °C.

25 The foamed products according to the invention are also storage stable. This means that the foamed product when stored at a temperature of from 4 to 25 °C for at least 7 days shows a specific volume which is at least 70 to 100% of the specific volume before storage. Furthermore storage stable products
30 preferably do not show an off flavour upon storage.
Flavour/taste and colour characteristics are determined by a panel test.

In a further aspect the invention relates to a foamed product comprising a dispersed gas phase and a liquid phase comprising an oxidised ferulyolated compound in an amount of from 1 wt% to 5 20 wt% on total weight of the liquid phase, said product being stable at ambient temperature.

A first insight in freeze-thaw stability and storage stability of foams can be obtained by visual inspection of the thawed 10 products. Foams which collapse or show a strong volume decline and/or substantial water release are not stable in the context of the invention.

The foamed products according to the invention are firm which 15 means they show a hardness value of at least 0.5 g, more preferred from 0.5 to 25 g, even more preferred from 8 g to 24 g, at room temperature (about 25 °C) under the measurement conditions indicated in the examples.

Preferably freeze-thaw stable foams show a difference in 20 hardness value of at most 20% compared to the hardness value before they were frozen and thawed under the conditions specified above.

According to a further aspect stable products (both with 25 respect to storage stability and freeze-thaw stability) do not show water release after the respective treatments. Water release is often seen on foam type products or emulsions and is referred to as syneresis.

The method to determine water release is described in the 30 examples. Preferred products show a water release of less than 0.2 ml/g determined by the method according to the examples.

More preferably the foams according to the invention show substantially no water release after storage or after a freeze-thaw treatment as specified above.

5 Examples of foamed products are whipped toppings, whipped cream, foamed shaving cream.

The foamed product comprises an oxidised ferulylated compound in the liquid phase. Ferulic acid groups (4-hydroxy-3-methoxy-
10 cinnamyl - groups) are known to be capable of crosslinking in the presence of certain oxidants (e.g. Oosterveld et al; oxidative crosslinking of pectic polysaccharides from sugar beet pulp, Carbohydrate research 328; 199-207, 2000). In the oxidation process a new covalent bond is formed between two
15 individual ferulic acid groups.

The compound comprising oxidised ferulylated groups is preferably a polymer, more preferred a polysaccharide. Examples of suitable polymers include pectin, arabinan, galactan,
20 cellulose derivatives, galactomannans such as guar gum, locust bean gum, starches or other polymers comprising hydroxyl groups which can be esterified to a ferulic acid group.

The polymers comprising ferulic acid groups can be naturally occurring or synthesised polymers. Examples of naturally
25 occurring polymers with ferulic acid groups are sugar beet pectin and arabinoxylanes isolated from cereals.

Synthetic processes to prepare polymers with ferulic acid groups generally include esterification of ferulic acid to a free hydroxyl group situated on the polymer backbone or on a
30 sugar substituent.

In a highly preferred embodiment, the foamed product comprises an oxidised pectin, even more preferred oxidised sugar beet pectin. The principal building units of pectin are smooth homogalacturonic regions and rhamnified hairy regions in which most neutral sugars are located. Arabinose is the predominant neutral sugar. Galactose is present in rhamnogalacturonan. 50-55% of the ferulic acid groups are linked to arabinose units and about 45-50% of the ferulic acid groups are linked to galactose residues.

10

Preferably 15 to 80 % of all ferulic acid groups are oxidised in the final foamed product.

It is preferred that the majority of ferulic acid groups is not oxidised before gas is incorporated in step (b). More preferred before step (b) at most 10% of all ferulic acid groups are oxidised.

The amount of oxidised ferulyolated compound in the liquid phase of the foamed product is from 1 to 20 wt%. Lower amounts were found not to provide sufficient firmness and storage stability was unsatisfactory. Higher amounts often do not dissolve at a satisfactory level and may lead to inclusion of the oxidant by oxidised polymers. This may inactivate the oxidant and may lead to phase separation.

25

Preferably the amount of oxidised ferulyolated compound is from 1 to 10 wt%, more preferred 1 to 4 wt%, even more preferred from 2 to 4 wt% on total liquid phase.

30 The liquid phase can be any liquid phase, but the presence of at least some water is required.

In a highly preferred embodiment, the liquid phase comprises water in an amount of at least 20 wt% on total weight of the liquid phase.

Examples of liquid phases which fulfil this requirement are
5 milk, cream, juices and certain oil in water and water in oil emulsions.

These liquid phases are preferred for the product according to the invention.

10 Optionally the liquid phase comprises an organic solvent such as ethanol.

Although the protein based foams as described in the prior art were as such found to be unstable upon freezing and thawing,
15 the current products may comprise some protein. Protein may serve to improve their nutritional value, their taste and appearance and foam volume especially if the foam is prepared at relatively low shear.

However care should be taken that the amount of protein is not
20 too high, which was found to lead to products which do not show the desired freeze-thaw stability.

Therefore the foamed product preferably comprises protein in an amount from 0.1 to 15 wt%, more preferred from 1 to 10 wt%,
25 even more preferred from 2 to 5 wt%, on total weight of the liquid phase.

Suitable proteins include whey protein, egg white protein, casein, other milk protein, soy protein, potato protein, rice
30 protein, shea protein, maize protein, barley protein or a combination thereof.

In a highly preferred embodiment the products according to the invention comprise a protein in an amount from 1 to 5 wt% and a ferulylated pectin in an amount from 1 to 4 wt%.

5 It is well known that fat present in an aqueous egg white composition prevents the whippability of the composition to a great extent. It has surprisingly been found that the current foams are stable and show the desired specific volume, even in the presence of oil or fat. It has been found that amounts of
10 fat or oil up to 60 wt% on the liquid phase volume are tolerable and do not severely reduce the foam firmness or its stability. Compared to a foam based only on ferulylated compound, without fat or oil, the compositions that contain oil or fat show a more creamy, mousse-like structure with less
15 overrun. For products comprising oil or fat the specific volume is preferably from 0.01 to 0.9 g/ml, preferably 0.1 to 0.9 g/ml.

The oil or fat is preferably selected from the group comprising
20 sunflower oil, coconut oil, butter fat, rapeseed oil, olive oil, peanut oil or oils extracted from plant or flower material such as rose oil, and combinations thereof. Also fractionated oils are encompassed in the invention.

25 The foamed product may optionally comprise further ingredients such as salt, flavour components, colourants, emulsifiers, acidifying agents, (co)-oxidants such as hydrogen peroxide, and the like. If particulate ingredients such as fruit pieces or nuts are added, it is preferred that these are added shortly
30 after the desired specific volume has been reached and while oxidation is at least ongoing. This is preferred because the particulate ingredients are then likely to be enclosed in the oxidised crosslinked network, which improves the stability of

the final foamed product and reduces the tendency of the particulate ingredients to precipitate on the bottom of a jar containing the foamed product.

5 In a further aspect the invention relates to a food product comprising a foamed product according to the invention. Examples of food products which suitably may incorporate the foamed product include ice cream, margarine, table spreads, butter, desserts, and yoghurt.

10

The invention is especially suitable for ice cream, milk ices and water ice products. Water ice, milk ice and ice cream will be referred to as frozen confection hereafter. Such products and processes to prepare these are for example disclosed in
15 "Ice Cream" by R.T. Marshall & W.S. Arbuckle, 5th Edition, 1996, Chapman & Hall, New York.

A frozen confection is a foamed, sweet product containing a large amount of ice. Frozen confections generally comprise sugars and sweeteners (such as sucrose and glucose), water and
20 optionally ingredients selected from the group comprising protein, fat, thickeners, emulsifiers and stabilisers. Furthermore taste and flavour components or preservatives are optionally included.

25 Water ice and milk ice are generally fat-free whereas ice cream preferably comprises from 2 to 20% fat. The overrun of frozen confections is preferably from 30 to 150%. The preferred overrun among others depends on the type of ice product. The overrun for water ice is generally lower than for ice cream.

30

In this preferred aspect a process is provided for preparing a frozen confection wherein

- a) a mixture of ingredients of the frozen confection and a ferulyolated compound in water is prepared at a preferred temperature of from 15 to 60 °C
- b) a gas phase is incorporated in this mixture
- 5 c) the mixture is mixed with an oxidant capable of oxidation of the ferulic acid groups in the ferulyolated compound, preferably under conditions wherein homogeneous distribution of the oxidant in the liquid is ensured
- d) the foam which results from step (c) is frozen at a
- 10 temperature below minus 4 °C, preferably from -50 to -10 °C.

The mixture of step (a) is preferably a homogeneous mixture of the ingredients in the frozen confection. The ingredients are described below.

15

In step (c) ferulic acid groups are linked by oxidation. This is carried out simultaneously with gas incorporation or more preferred after incorporation of gas in step (b).

- 20 Preferably the oxidation in step (c) is continued for some time, preferably in the order of 1-10 minutes, to allow the product to reach maximum stability. Hence it is preferred that freezing is not done immediately after step (c) but after the foamed mixture has been allowed to stand for at least about 1
- 25 minute.

Optionally a homogenisation and/or pasteurisation and/or sterilisation step is included before step (b).

- 30 The temperature during step (b) and (c) can be any suitable temperature. A temperature from (minus)-20 °C to +15 °C, preferably from -15 °C to + 5 °C is preferred. Optionally the product is already partly frozen before step (d).

The preferred characteristics of the foamed product described above equally apply to the process for preparing a frozen confection.

5

In a further aspect the invention relates to a frozen confection, preferably ice cream obtainable by this process.

The preferred ferulyolated compound is (sugar beet) pectin,
10 preferably in an amount of from 0.8 to 5 wt%, more preferred from 1 to 4 wt% on total weight of the frozen confection.

Ice cream preferably comprises about 2 to 7 wt% protein which are usually added as part of whey powder or skim milk powder.
15 Common sweeteners that are optionally included are preferably selected from the group comprising sucrose, glucose, lactose, corn syrups or a combination thereof.

Stabilisers are preferably selected from the group comprising guar gum, locust bean gum, carrageenan, starch, gelatin or a
20 combination thereof. Preferred amount is from 0.1 to 1 wt% on product.

Preferred emulsifiers are selected from the group comprising saturated monoglycerides, saturated diglycerides of fatty
25 acids, polyglycerol esters, sorbitan esters, stearyl lactylate, lactic acid esters, citric acid esters, acetyllated monoglyceride, diacetyl tartaric acid esters, polyoxyethylene sorbitan esters, lecithin, egg yolk, or a combination thereof. Preferred amount is from 0.05 to 0.5 wt% on product.

30

Optionally the frozen confection comprises colour or flavour components. A well known flavour component for ice cream is for example vanillin. Care should be taken that vanillin is

preferably added after the oxidation in step (c) has been completed because of the structural similarity of ferulic acid and vanillin. Addition of vanillin before oxidation may perturb the oxidation reaction. Alternatively the vanillin level is
5 sufficiently low compared to the amount of ferulylated compound such that the oxidation reaction is not disturbed. It was further found that the presence of fat in which vanillin easily dissolves, may reduce any negative influence of vanillin on the oxidation of ferulic acid residues.

10

The stability of these ice confections is preferably determined by a so called meltdown test which is described in the examples.

15 In an alternative embodiment, the invention relates to creamy or pastey products comprising the foamed product. Examples of such products include shaving cream and skin cream.

The invention is illustrated by the following examples.

20

Examples

General techniques that were applied

5 1. Measurement of hardness

Apparatus used: Texture Analyser model LFRA 1000g/100g from CNC Farnell. Unit 1 Manor place Manor Way, Boreham Woods, Herts, UK.

Probe used: probe made of synthetic material,

10 probe size: diameter 25 mm, height 35 mm.

Settings of the Texture analyser:

Penetration speed: 2 mm/sec

Distance: 10 mm

The hardness value is determined in grams.

15 The temperature is 25°C.

2. Determination of specific volume (S.V.)

The specific volume of the foamed product was measured by filling a calibrated cup with known volume and weight and

20 leveling the top. The weight of the filled cup was measured. SV is the ratio between the volume of the foamed product in the cup and the weight of the foamed product in the cup expressed as g/ml.

25 3. Determination of water release

Calibrated 50 ml tubes were completely filled with foam.

Water release (water layer on bottom of tube) was

determined. The weight of the foam was determined by

weighing the empty and the filled tube. Water release is

30 expressed as ml water released per gram of foam.

4. Activity assay

Add 100 µl 20 mM ABTS (2,2'-azino-bis(3-ethylbenzothiazoline-6-sulfonic acid (ABTS) stock solution made in indicated buffer) to 880 µl 25 mM phosphate buffer, pH 6.0. Incubate for 5' at 30 °C. Add 10 µl 100 mM hydrogen peroxide. Start
5 the reaction by addition of 10 µl enzyme (diluted in such a way that a linear curve could be measured). Measure the formation of ABTS radical at 414 nm using a spectrophotometer.

Specific activity is defined as: µmol ABTS oxidised per minute
10 per mg protein at pH 6.

Example 1-2

Materials:

- 15 - 12.5 wt% egg white solution (prepared from High-Whip powder, van Enthoven) in water
- 4 wt% sugar beet pectin solution in water
- 100 mM hydrogen peroxide
- 0.106 mg/ml (specific activity = 6.10 exp 5 units per mg at
20 pH 6) ARP (peroxidase from *Arthromyces Ramosus*.
- Horseradish peroxidase (HRP) stock solution 0.6 mg/ml
specific activity 3.2 exp 4 units per mg.

Experiments were performed in glass 10 ml tubes. An ultra-
25 turrax was used at the highest speed. All the components, except for the enzyme, were mixed and briefly (1-2 seconds) submitted to high shear with a Turraxtm mixer at the highest speed. Then the enzyme was added (during shear). When the foam had been formed (after a few seconds), the shear treatment was
30 stopped so that the enzyme could fix the foam.

Table 1; composition examples 1-2

Sample no.	Water (µl)	4% pectin solution (µl)	12.5% egg white solution (µl)	100 mM hydrogen peroxide (µl)	ARP (µl)
1	1000	1000	-	20	40
2	680	1000	320	20	40

Results examples 1-2:

Table 2

sample no.	Freeze-thaw stable	Visual characteristics	Storage stability at 20 °C
1	yes	White foam	good
2	yes	White foam	good

5

Example 3-7

Materials:

- Sunflower oil
- 10 - 4% sugar beet pectin solution, sugar beet GENU pectin type BETA from CP Kelco (Denmark) product info number 1005-19, batch no 02995.
- 100 mM hydrogen peroxide
- 0.106 mg/ml ($2 \cdot 10^4$ ABTS units at pH 6) ARP (peroxidase from
- 15 *Arthromyces ramosus* stock solution 0.106 mg/ml, activity $2.10 \cdot 10^4$ ABTS units per ml).

Process

Oil-in-water: pectin, water and hydrogen peroxide were mixed 20 and then submitted to high shear with a Turraxtm mixer at the

highest speed. During shear treatment the oil was added slowly. When all the oil had been added, ARP was added.

Water-in-oil: pectin, water and hydrogen peroxide were mixed separately (water phase). The oil phase was submitted to high shear with a Turraxtm mixer at the highest speed and the water phase was added slowly. When the complete water phase was added, ARP was added to the emulsion.

Experiments were performed in small glass jars (~10 ml). The ultra-turraxtm (Janke & Kunkel, IBA labortechnik) T25, 24000 rpm was used at the highest speed.

Table 3

Sample no.	water (µl)	4% pectin (µl)	sunflower oil (µl)	100 mM hydrogen peroxide (µl)	ARP (µl)	HRP (µl)
3	1600	2000	400	40	80	-
4	1600	2000	400	40	-	14
5	1200	2000	800	40	80	-
6	400	2000	1600	40	80	-
7	400	2000	1600	40	80	-

Example number 7 resulted in a water in oil emulsion, the others were oil in water emulsions.

15

Results:

Table 4

sample no.	% oil	Visible characteristics of product	Stability (after 3 days at 20 °C)
3	10	white, firm	little water release
4	10	white, firm	see 3
5	20	white, firm	little water release but less than in 3 and 4
6	40	white, firm	no oil release
7	40	white, firm	no oil release

The firm white structure that was formed looked creamy, was tasteless and felt soft in the mouth.

Examples 8 - 9

5 The procedure of example 1 and 2 was used, with the ingredient composition as outlined below. In stead of an ultraturrax, a Hobart™ mixer at maximum speed (3) was used for foam formation before oxidation. The Hobart™ mixer used was a model N5D at maximum speed (1425 rpm) equipped with a wired whisk (B flat
10 beater). ARP was added immediately when a foam had been formed after which mixing was continued for about 15 seconds. The time of shear treatment in the Hobart™ mixer was 5 minutes for example 8 and 9.

15 Table 5 ; composition examples 8 and 9

Sample no.	Water (ml)	4% pectin solution (ml)	12.5% egg white solution (ml)	1 M hydrogen peroxide (ml)	ARP (ml)
8	125	125	-	0.25	5
9	85	125	40	0.25	5

Results examples 8 and 9

Table 6

sample no.	Freeze -thaw stable	SV before thawing	hardness value at 25 °C	Visual characteristics	Water release after 24 hours
8	yes	0.81 g/ml	25.5	White foam	0.13 ml/g

9	yes	0.14 g/ml	14	White foam	0.16 ml/g
---	-----	-----------	----	---------------	--------------

It was concluded that in the presence of some egg white, a higher specific volume can be obtained. However these products are less stable and less firm although they still show the 5 desired firmness and stability.

Example 10

0.2 g sodiumbicarbonate and 0.26g disodiumpyrophosphate were 10 added to 10 ml 4% sugar beet pectin (the same as described in ex. 3-7) solution under stirring with a magnetic stirrer bar. Immediately after the salts were added, 80 µl polyporus pinctus laccase was added (6.6 mg/ml, 22 Units/mg) to obtain oxidising of the ferulic acid groups of pectin. 15

The resulting product was a stable foam.

Comparative examples (not according to the invention)

20 Comparative examples A - C Composition

Table 7

Sample no.	Water (µl)	4% pectin (µl)	12.5% egg white (µl)	100 mM hydrogen peroxide (µl)	ARP (µl)
A	-	-	2000	-	-
B	1680	-	320	-	-
C	680	1000	320	-	-

Comparative example A-C Results

Table 8

sample no.	Freeze-thaw stable	Storage stability at 20 °C
A	no	Instable
B	No	Instable
C	No	instable

After 5 minutes at room temperature in samples A, B, C, a liquid layer was formed under the foam. After about 30 minutes this effect had slightly increased.

Therefore it is concluded that the lack of fixing of the foam structure by oxidation, leads to instable products, not fulfilling the requirements of the invention.

10 Comparative example D-F

Table 9

Sample no.	water (µl)	4% pectin (µl)	sunflower oil (µl)	100 mM hydrogen peroxide (µl)	ARP (µl)	HRP (µl)
D	1600	2000	400	40	-	-
E	1200	2000	800	40	-	-
F	-	2000	2000	40	80	-

Results comparative example D-F

Table 10

sample no.	% pectin	% oil	result	Stability (after 3 days)
D	2%	10	white, fluid	
E	2%	20	white, fluid	complete phase separation
F	2%	50	white, fluid	complete phase separation

On the basis of these results it was concluded that high amounts of oil outside the claimed range, leads to instable products. Furthermore if no oxidant is present, there is either
5 no foam formation or the formed foam is instable.

Comparative example G, H, I

The procedure of comparative example A and B was used, with the ingredient composition as outlined below. In stead of an
10 ultraturrax, a Hobart mixer at maximum speed (3) was used for foam formation before oxidation.

Table 11; composition comparative examples G, H, I

Sample no.	Water (ml)	4% pectin solution (ml)	12.5% egg white solution (ml)	1 M hydrogen peroxide (ml)
G	210	125	-	0.25
H	85	125	40	-
I	-	-	125	-

15 Results comparative examples G, H, I

Table 12

sample no.	Freeze -thaw stable	SV before thawing	hardness value at 25 °C (g)	Water release after 24 hours (ml/g)
G	No	0.11 g/ml	26.5	0.93
H	No	0.088 g/ml	15.5	0.82
I	no	0.073	7	0.95

On the basis of these experiments it was concluded that the absence of oxidant or the use of a not powerful oxidant such as hydrogenperoxide as such, leads to the formation of products which are not freeze-thaw stable.

5

Example 11

The formulation shown in Table 13 was prepared. This base mix was then aerated (a) with the cross-linking of the pectin and
 10 (b) without the cross-linking of the pectin (comparative example). The aerated mixes were then frozen, and the improved temperature stability of the ice cream products was demonstrated using a meltdown test.

15 Table 13: Formulation of the base mix

Ingredient	wt. %
Skimmed Milk Powder (Sunsheaf, ca. 35% protein)	7.4
Whey Powder ("Espiron 300", DMV Int., ca. 30% protein)	2.6
Sucrose (Tate and Lyle)	15.6
Coconut Oil ("HARDKO", Loders Crokiaan)	12
Saturated Mono-/di- glycerides ("Admul MG40-04, Quest Int.)	0.39
Vanilla Flavour (Quest Int.)	0.05
β -carotene (Roche)	0.01
Sugar Beet Pectin ("Genu® Beta pectin", CP Kelco)	2
Water	to 100%

Mix preparation

The pre-mix is the unhomogenised, unpasteurised mixture of ingredients. 40 kg of pre-mix was made up by adding milk powders, sugars and stabiliser to water at 55°C. In these formulations, emulsifiers were dissolved in molten fat before the mixture was blended with the aqueous ingredients.

The pre-mix was then heated to 82°C with a plate heat exchanger, followed by homogenisation with a single stage valve homogeniser (APV Crepaco Homogeniser F-8831 3DDL) at 140 bar pressure. The pre-mix was then pasteurised at this temperature for 25 seconds. The mix was cooled to 5°C with a plate heat exchanger, and then collected in a 50 kg stainless steel churn, and stored at 2°C.

15 Aeration of the mix

From this base mix (formulation shown in Table 13), three aerated mixes were produced. 4 kg batches of mix were aerated using a Hobart mixer set at speed setting 3. The mixes were all aerated to approximately 100 % overrun. To achieve 100% OR took approximately 8 minutes of continuous whipping. Cross-linking agents were added as follows:

Mix 1. With no cross-linking of the pectin during aeration (i.e. no addition of enzyme and hydrogen peroxide).

Mix 2. Where the pectin was cross-linked during aeration by the addition of 0.175 wt.% Biobake Wheat (peroxidase) to the mix, followed by 0.2% (w/v) of 1 mol dm⁻³ hydrogen peroxide before aeration began.

Mix 3. Where the pectin was cross-linked after aeration by the addition of 0.175 wt.% Biobake Wheat (peroxidase) to the mix, followed by 0.2% (w/v) of 1 mol dm⁻³ hydrogen peroxide to the aerated mix. Further mixing (20 s) was used to incorporate the ingredients evenly.

(Biobake Wheat is an enzyme preparation from Quest International that contains soy bean peroxidase with an activity of 2000 units per g.)

10

Following aeration, the products were collected in 500 mL wax-coated cartons, and frozen at - 25°C.

Experimental Procedure for Meltdown Tests

15

Tests were performed on a stainless steel wire mesh grid having a size of 25 x 25 cm, with 5 mm holes, 1mm thick wire. Underneath the grid was disposed a collecting vessel (of large enough volume to collect the entire sample tested) and balances for weighing the material collected in the vessel. The balances are connected to a data logging system to record the mass collected. The grids were placed in a meltdown cabinet set at a constant temperature environment 37°C and which was capable of holding up to 12 of these grids simultaneously. Trays of water were placed within the cabinet to increase humidity and prevent any samples placed therein from drying.

Before placement in the cabinet the ice cream samples were equilibrated in a freezer at -25°C, and then weighed on a zeroed balance. They were then placed on the mesh grid and were arranged randomly over the available positions in the meltdown cabinet. Once all samples were in place, the data logging

30

system measured the amount of collected material every minute over a 240 minute time period.

From the mass of the sample collected over this period, the percentage mass loss of the samples is calculated using the following formula.

$$\% \text{MassLoss} = \frac{M_t - M_0}{F} \times 100$$

wherein;

- 10 M_t = mass recorded (gram) at time t minute
 M_0 = mass recorded (gram) at start of analysis, t = 0 minute
 F = Initial mass of product (gram)

The % mass loss (%ML) for two samples of each formulation was averaged. From these data, the initiation time ($t^{4\%}$) for each
15 sample of formulation was calculated. This is defined by the time that elapses before a percentage mass loss of 4% is achieved.

Results of the meltdown test

Initiation times for the mixes, and mass loss after 120 and 240 minutes are summarised in Table 14.

5

Table 14 Initiation time and mass loss data for the three ice cream products.

Mix	Initiation time ($t^{4\%}$) / minute	Mass loss after 120 minutes / %	Mass loss after 240 minutes / %
1	12	93	92
2	-	0	0
3	-	0	0

10 From these data, it is concluded that the cross-linking of the pectin (both during and after aeration) leads to a significantly more stable foam compared to the same formulation containing pectin which is not cross-linked. Mix 1, where no cross-linking of the pectin occurs, shows rapid meltdown
15 behaviour. Mixes 2 and 3, where cross-linking of the pectin does take place, show no appreciable meltdown whatsoever over the 240 minute time period.

The presence of a low amount of vanillin, in combination with
20 the oil, did not negatively influence the final product.

Claims

1. Process for the preparation of a foamed product comprising the steps of:
 - a) providing a mixture of a liquid and a ferulylated compound
 - b) incorporating a gas phase in this mixture
 - c) combining said mixture with an oxidant capable of oxidation of the ferulic acid groups in the ferulylated compound, preferably under conditions wherein homogeneous distribution of the oxidant in the liquid is ensured.
2. Process according to claim 1 wherein the gas phase is incorporated by a method selected from the group comprising subjecting the mixture to high shear treatment, addition of a leavening system under conditions where leavening takes place, addition of an enzymatic system which leads to gas formation.
3. Process according to any of claims 1-2 wherein the oxidant is an enzyme or enzymatic system.
4. Process according to any of claims 1-3 wherein the temperature in step (b)- (c) is between -20 °C and 40 °C, preferably 4 to 20 °C.
5. Process according to any of claims 1-4, which additionally comprises a drying step.
6. Foamed product obtainable by the process according to any of claims 1-4 said product comprising a dispersed gas phase and a liquid phase comprising an oxidised ferulylated compound in an amount of from 1 wt% to 20 wt% on total weight of the

liquid phase.

7. Foamed product according to claim 6 wherein the liquid phase comprises water in an amount of at least 20 wt% on total weight of the liquid phase.
8. Foamed product according to any of claims 6-7 wherein the liquid phase is selected from the group comprising water, milk, cream, juices, oil in water and water in oil emulsions.
9. Foamed product according to any of claims 6-8 which comprises protein in an amount from 0.1 to 20 wt% on total weight of the liquid phase.
10. Foamed product according to any of claims 6-9 which comprises up to 60 wt% oil on total weight of the liquid phase.
11. Foamed product according to any of claims 6-10 having a specific volume of from 0.01 to 0.9 g/ml.
12. Foamed product according to any of claims 6-11 wherein the ferulylated compound is a pectin.
13. Foamed product according to claim 12 wherein the ferulylated compound is sugar beet pectin.
14. Foamed product obtainable by the process according to claim 5.

15. Food product comprising a foamed product according to any of claims 6-14.
16. Shaving cream comprising a foamed product according to any of claims 6-14.
17. A process for preparing a frozen confection wherein
- a) a mixture of ingredients of the frozen confection and a ferulylated compound in water is prepared at a preferred temperature of from 15 to 60 °C
 - b) a gas phase is incorporated in this mixture
 - c) the mixture is mixed with an oxidant capable of oxidation of the ferulic acid groups in the ferulylated compound, preferably under conditions wherein homogeneous distribution of the oxidant in the liquid is ensured
 - d) the foam which results from step (c) is frozen at a temperature below minus 4 °C, preferably from -50 to -10 °C.
18. Frozen confection obtainable by the process according to claim 17.

INTERNATIONAL SEARCH REPORT

International Application No

PCT/EP 02/01212

A. CLASSIFICATION OF SUBJECT MATTER

IPC 7 A23L1/0524 A23L1/10 A23P1/16 A61K7/15 A21D13/08
A23G9/02 A62D1/00

According to International Patent Classification (IPC) or to both national classification and IPC

B. FIELDS SEARCHED

Minimum documentation searched (classification system followed by classification symbols)

IPC 7 A23L A23P A61K A21D A23G A62D

Documentation searched other than minimum documentation to the extent that such documents are included in the fields searched

Electronic data base consulted during the international search (name of data base and, where practical, search terms used)

EPO-Internal, WPI Data, PAJ, FSTA

C. DOCUMENTS CONSIDERED TO BE RELEVANT

Category *	Citation of document, with indication, where appropriate, of the relevant passages	Relevant to claim No.
X	WO 00 40098 A (DANISCO ; JUUL ANNE GRETE (DK); NOERBOEGE LISE (DK); SOENDERGAARD K) 13 July 2000 (2000-07-13)	6-16, 18
Y	page 5, line 17 - page 9, line 21 page 11, line 24 - page 14, line 8; claims 1, 6-8, 10-13; examples 1, 3, 4	1-5, 17
X	WO 99 11672 A (FITCHETT COLIN STANLEY ; DU PONT (US)) 11 March 1999 (1999-03-11) page 3, line 4 - line 25 page 14, line 15 - page 15, line 27 page 18, line 1 - page 19, line 34 page 20, line 10 - line 11	1-18



Further documents are listed in the continuation of box C.



Patent family members are listed in annex

* Special categories of cited documents :

A document defining the general state of the art which is not considered to be of particular relevance

E earlier document but published on or after the international filing date

L document which may throw doubts on priority claim(s) or which is cited to establish the publication date of another citation or other special reason (as specified)

O document referring to an oral disclosure, use, exhibition or other means

P document published prior to the international filing date but later than the priority date claimed

T later document published after the international filing date or priority date and not in conflict with the application but cited to understand the principle or theory underlying the invention

X document of particular relevance; the claimed invention cannot be considered novel or cannot be considered to involve an inventive step when the document is taken alone

Y document of particular relevance; the claimed invention cannot be considered to involve an inventive step when the document is combined with one or more other such documents, such combination being obvious to a person skilled in the art.

G document member of the same patent family

Date of the actual completion of the international search

12 July 2002

Date of mailing of the international search report

29/07/2002

Name and mailing address of the ISA

European Patent Office, P.B. 5818 Patentlaan 2
NL - 2280 HV Rijswijk
Tel. (+31-70) 340-2040, Tx. 31 651 epo nl,
Fax (+31-70) 340-3016

Authorized officer

Vernier, F

INTERNATIONAL SEARCH REPORT

International Application No

PCT/EP 02/01212

C.(Continuation) DOCUMENTS CONSIDERED TO BE RELEVANT

Category *	Citation of document, with indication, where appropriate, of the relevant passages	Relevant to claim No.
Y	US 5 384 145 A (GONSALVES ALEXANDER A ET AL) 24 January 1995 (1995-01-24) cited in the application column 1, line 37 -column 3, line 48; claim 1; example ---	1,2,4,5
Y	WO 96 03440 A (NOVONORDISK AS ;BUDOLFSEN GITTE (DK); HELDT HANSEN HANS PETER (DK)) 8 February 1996 (1996-02-08) cited in the application page 6, line 34 -page 8, line 8 page 9, line 20 -page 10, line 16 page 11, line 8 -page 12, line 18; claims 1,4,9,10 ---	1-18
Y	WO 94 17137 A (NUSSINOVITCH AMOS ;YISSUM RES DEV CO (IL); RAPAPORT ERICH (IL)) 4 August 1994 (1994-08-04) page 2, line 20 -page 5, line 8; claims 1-3,8,9; example 3 ---	2
Y	EP 0 426 434 A (SBP INC ;ST LAWRENCE REACTORS LTD (CA)) 8 May 1991 (1991-05-08) page 2, line 9 - line 19 page 5, line 14 -page 6, line 44; example 3 ---	1-18
Y	FR 2 545 101 A (AGRONOMIQUE INST NAT RECH) 2 November 1984 (1984-11-02) page 2, line 10 -page 5, line 20; claims; examples ---	1-18
A	US 4 510 166 A (LENCIN JULIANNE M ET AL) 9 April 1985 (1985-04-09) column 2, line 27 -column 3, line 42; claims 1,2,12,13; example 1 ---	1-18
A	GUILLON F ET AL: "Characterization and oxidative cross-linking of sugar beet pectins after mild acid hydrolysis and arabanases and galactanases degradation." , FOOD HYDROCOLLOIDS 1987 LAB. DE BIOCHIMIE ET TECH. DES GLUCIDES, RUE DE LA GERAUDIERE, 44072 NANTES CEDEX 03, FRANCE, VOL. 1, NR. 5/6, PAGE(S) 547 - 549 XP001087730 the whole document -----	1-18

INTERNATIONAL SEARCH REPORT

Information on patent family members

International Application No

PCT/EP 02/01212

Patent document cited in search report		Publication date	Patent family member(s)	Publication date
WO 0040098	A	13-07-2000	AU 1887300 A WO 0040098 A1	24-07-2000 13-07-2000
WO 9911672	A	11-03-1999	AU 9122398 A CN 1268955 T EP 1015498 A1 WO 9911672 A1 ZA 9807913 A	22-03-1999 04-10-2000 05-07-2000 11-03-1999 29-02-2000
US 5384145	A	24-01-1995	BR 9402762 A CA 2112139 A1 EP 0648429 A1	04-04-1995 20-02-1995 19-04-1995
WO 9603440	A	08-02-1996	AT 198604 T AU 3074595 A BR 9508350 A CA 2195640 A1 CZ 9700205 A3 DE 69519852 D1 DE 69519852 T2 WO 9603440 A1 EP 0750641 A1 ES 2155523 T3 FI 970274 A HU 77999 A2 JP 10502962 T PT 750641 T US 6232101 B1	15-01-2001 22-02-1996 04-11-1997 08-02-1996 14-05-1997 15-02-2001 02-08-2001 08-02-1996 02-01-1997 16-05-2001 23-01-1997 28-04-1999 17-03-1998 29-06-2001 15-05-2001
WO 9417137	A	04-08-1994	IL 104441 A AU 5884094 A WO 9417137 A1	28-01-2001 15-08-1994 04-08-1994
EP 0426434	A	08-05-1991	US 5008254 A AT 146190 T AU 630755 B2 AU 6564190 A CA 2029022 A1 DE 69029365 D1 DE 69029365 T2 DK 426434 T3 EP 0426434 A1 ES 2098257 T3 GR 3022784 T3 JP 3197502 A	16-04-1991 15-12-1996 05-11-1992 09-05-1991 02-05-1991 23-01-1997 10-04-1997 30-12-1996 08-05-1991 01-05-1997 30-06-1997 28-08-1991
FR 2545101	A	02-11-1984	FR 2545101 A1 DE 3461938 D1 EP 0124439 A2 JP 59205949 A US 4672034 A	02-11-1984 12-02-1987 07-11-1984 21-11-1984 09-06-1987
US 4510166	A	09-04-1985	AT 63204 T AU 549987 B2 AU 3697284 A CA 1226167 A1 DE 3484562 D1 DK 25985 A	15-05-1991 20-02-1986 25-07-1985 01-09-1987 13-06-1991 20-07-1985

INTERNATIONAL SEARCH REPORT

Information on patent family members

International Application No

PCT/EP 02/01212

Patent document cited in search report	Publication date	Patent family member(s)	Publication date
US 4510166	A	EP 0149258 A2	24-07-1985
		JP 60164449 A	27-08-1985
		JP 6105652 A	19-04-1994
		ZA 8409843 A	28-08-1985
